

NEW RELEASE

STELVIO 1800



Battery Voltage	IU1a Wet 8h Range (C5)	IU1a Wet 12h Range (C5)	IU1a Gel PzV 10-14h Range (C5)	Charging Current	Model
24V	280+340 Ah	450+550 Ah	350+420 Ah	50A	24-50
	340+410 Ah	540+660 Ah	420+510 Ah	60A	24-60
36V	230+280 Ah	360+440 Ah	275+340 Ah	40A	36-40
48V	170+210 Ah	270+330 Ah	210+255 Ah	30A	48-30

CHARGING PHASE



CHARGING COMPLETED



ANOMALY



Main features:

Power up to 1.8 kW

24V up to 48V

30A up to 60A

Flexible compact charger with premium features

Available on-board (-E)

off-board (-W)

DIMENSIONS (LxWxH): 377 x 188 x 79 mm

14.8 x 7.40 x 3.11 in

WEIGHT: 5,5 Kg – 12,13 lbs

PROTECTION GRADE IP20

INPUT VOLTAGE: 200-240 Vac

Main features:

- **SLIM FORM FACTOR FOR ON BOARD and OFF BOARD INSTALLATION**
- **ACTIVE PFC**
- **INPUT VOLTAGE : 200-240 Vac 50-60 Hz**
- **RESONANT TECHNOLOGY**
- **HIGH EFFICIENCY: > 90%**
- **SUITABLE FOR LEAD (WET/GEL/AGM) and LITHIUM BATTERIES**
- **BATTERY THERMAL PROBE I/O (OPT.)**
- **REMOTE LED (OPT.)**
- **INTERLOCK (NO/NC)**
- **AUXILIARY OUTPUT RELAY**
- **CANBUS – RS485**
- **REAL TIME CALENDAR (OPT)**
- **WALL MOUNTING HOLES for easy wall mount**

